

Product No: SL2-485-EC90

NOVARIS SL2-485-EC90 SURGE PROT. DEVICE SL2-485-EC90

FEATURES

- - Plug-in signal line protector
- - Multistage protection
- - For most twisted pair signalling schemes
- - Visual indicator & Alarm contacts



General Information

Brand	NOVARIS
Product Type	Signal Line Protector
Series	SL2

Technical Attributes

Connection Type	Series
Maximum Continuous Operating Voltage MCOV AC (V)	6
Maximum Continuous Operating Voltage MCOV DC (V)	8
Maximum Discharge Current (10/350 μ s) - I _{max} (kA)	5/Line
Maximum Discharge Current (8/20 μ s) - I _{max} (kA)	10/Line
Maximum Load Current - I _N (A)	0.25
Tightening Torque (Nm)	0.5

Physical Attributes

Housing Material	Polycarbonate
Mounting Type	TS35 DIN Rail
Operational Temperature Range (°C)	-40 to +70

Dimensions

Dimensions (mm)	110L X 12W X 71H
-----------------	------------------

Protection & Standards



Degree of Protection	IP20
Standards and Approvals	IEC 61643-21:2012, AS/NZS 1768:2007

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------

TECHNICAL DRAWING

