

Product No: OTP63A3M

ABB OTP63A3M SAFETY SWITCH OTP63A3M

FEATURES

- Polycarbonate enclosure IP65
- Red-yellow selector handle (I-O/ON-OFF)
- Threaded knock-out openings
- N-, PEterminals included
- Grey enclosure



| General Information | |
|---------------------|---------------------------------|
| Brand | ABB |
| Product Type | Enclosed |
| Suitable For | Distribution Board Installation |
| Туре | Main Switch |

| Technical Attributes | |
|--|-----|
| Conventional Thermal Current - Ithe (A) | 115 |
| Maximum Operational Voltage AC (V) | 750 |
| No. of Normally-open Auxiliary Contacts | 1 |
| No. of Poles | 3 |
| Rated Operational Current AC-22A 415V (A) | 63 |
| Rated Operational Current AC-22A 500V (A) | 63 |
| Rated Operational Current AC-23A 380-415V (A) | 63 |
| Rated Operational Current AC-23A 415V (A) | 63 |
| Rated Operational Current AC-23A 500V (A) | 50 |
| Rated Operational Power AC-23A 380-415V (kW) | 30 |
| Rated Operational Voltage (V) | 750 |
| Rated Short-Time Withstand Current - Icw (kA) | 2.5 |
| Rated Short-time Withstand Current - Icw (kA/ls) | 2.5 |
| Rated Uninterrupted Current - Iu (A) | 115 |

| Physical Attributes | |
|------------------------|---------------------|
| Cable Outlets per Side | 2xM32+M16/2xM32+M16 |
| Control Element Colour | Red |



| Physical Attributes | |
|---------------------|------------|
| Enclosure Material | Plastic |
| Handle Colour | Red/Yellow |
| Handle Type | Selector |

| Dimensions | |
|-----------------|-------------------|
| Dimensions (mm) | 145W x 200H x 90D |
| Weight (kg) | 2.3 |

| Protection & Standards | |
|---------------------------|------|
| Degree of Protection | IP65 |
| NEMA Degree of Protection | 1 |