

Product No: DBM1255FM

DEHN DEHNBLOC M FM LIGHTNING CURRENT ARRESTER DBM1255FM

FEATURES

- Pluggable, coordinated and modular
- Single-pole lightning current arrester
- High follow current limitation
- Remote signalling contact
- Type 1 SPD according to EN 61643-11
- RADAX Flow spark gap technology
- Fault indication
- Energy-coordinated according to IEC 62305-4



General Information

Article No.	961125
Brand	DEHN
Product Type	Surge Protection Device

Technical Attributes

Circuit Type	MSB
Follow Current Extinguishing Capability AC (kArms)	50
Integral Fuse	No
Lightning Impulse Current (10/350 μ s) - Iimp (kA)	50
Maximum Continuous Operating Voltage MCOV AC (V)	255
No. of Poles	1P+N/PE(N)
Nominal Voltage AC (V)	230
Operating State/Fault Indication	Green/Red
Response Time (ns)	≤ 100
Signal C/O Contact	Yes
Voltage Protection Level - Up (kV)	≤ 2.5

Physical Attributes

Mounting Type	DIN Rail
---------------	----------

Dimensions

Dimensions (mm)	0.07W x 0.1L x 0.04D
No. of Modules	2
Weight (kg)	0.36

Protection & Standards

Degree of Protection	IP20
----------------------	------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------