

## Product No: CPI-10L-10

### ABB NON-ILLUMINATED PUSHBUTTON BLUE 1 NO CPI-10L-10

#### FEATURES

- Compact, space-saving design
- Durable, high dust and water resistance
- Ideal for quick activation
- Non-illuminated blue indication



#### General Information

|                       |  |
|-----------------------|--|
| Brand                 | ABB  |
| Enclosure Type (NEMA) | Type1, Type12, Type13, Type3R, Type4, Type4X |
| Product Type          | Pushbutton                                   |

#### Technical Attributes

|  |   |
|--|---|
| Connecting Capacity                      | Flexible with Ferrule 1/2 x 0.5 - 1.5mm <sup>2</sup><br>Flexible with Insulated Ferrule 1/2 x 0.5 - 1.5mm <sup>2</sup><br>Flexible 1/2 x 0.5 - 1.5mm <sup>2</sup><br>Solid 1/2 x 0.5 - 1.5mm <sup>2</sup> |
| Connection Type                          | Screw Clamp   |
| Function                                 | Momentary   |
| No. of Normally-open Contacts            | 1   |
| Power Loss (W)                           | Maximum 2.5W  |
| Rated Frequency (Hz)                     | 50/60   |
| Rated Impulse Withstand Voltage (kV)     | 6   |
| Rated Insulation Voltage (V)             | 300   |
| Rated Operational Current AC-15 240V (A) | 1   |
| Rated Operational Current DC-13 125V (A) | 0.2   |
| Rated Operational Current DC-13 24V (A)  | 0.3   |
| Rated Operational Voltage (V)            | 300   |
| Terminal Type                            | Screw   |
| Tightening Torque (Nm)                   | 0.8   |
| Wire Stripping Length (mm)               | 6   |

### Physical Attributes

|                                |                      |
|--------------------------------|----------------------|
| Actuator Type                  | Flush                |
| Ambient Temperature Range (°C) | -25 to 70            |
| Colour                         | Blue                 |
| Material                       | Bezel: Black Plastic |
| Storage Temperature Range (°C) | -40 to 85            |

### Dimensions

|                 |                 |
|-----------------|-----------------|
| Dimensions (mm) | 30W x 30H x 55D |
| Weight (kg)     | 0.018           |

### Protection & Standards

|                      |   |
|----------------------|---|
| Degree of Protection | Front: IP66, IP67, IP69K; Terminals: IP20 |
| Pollution Degree     | 3   |

### Resources

|                              |                                    |
|------------------------------|------------------------------------|
| Product catalogue (Flipbook) | <a href="#">Download from here</a> |
|------------------------------|------------------------------------|