

## Product No: 101150623

### SCHMERSAL ENCLOSED SAFETY SWITCH 101150623

*Note: For lengths of over 10 m, intermediate wire supports must be installed every 3 to 5 m. | Recommended cable lengths for pull-wire Emergency-Stop switches in relation to the range of ambient temperature. | As the thimbles are subject to deformation in case of wire pull, the wire should be pulled several times after fitting. After that, the wire must be re-tensioned using the eyebolt or the tensioner. | The screwed G24-M20 indicator lamp must be ordered separately, see accessories.*



#### General Information

Brand	SCHMERSAL
Cable Note	All indications including the conductor ferrules.
Coding Level According to EN ISO 14119	Low
EAN	4030660000000
eCl@ss Number, Version 11.0	27-37-12-38
eCl@ss Number, Version 9.0	27-27-26-03
ETIM 6.0	EC002593
ETIM 7.0	EC000222
Housing Construction Form	Norm construction design
Product Type	Switch
Working Principle	Mechanical

#### Technical Attributes

No. of Auxiliary Contacts	1
Contact Material	Silver
Maximum Actuating Speed (m/s)	0.3
Maximum Cable Cross Section (mm <sup>2</sup> )	1.5
Maximum Fuse Rating	4 A gG D-fuse
Minimum Actuating Speed (mm/min)	60
Minimum Cable Cross Section (mm <sup>2</sup> )	2 x 0.75
Minimum Mechanical Life	100000000 Operations
Minimum Positive Break Force (N)	20

No. of Safety Contacts	1
Overvoltage Category	3
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	500
Rated Short-circuit Current (A)	1000
Resistance to Shock (g/ms)	30 / 11
Switching Element	Opener (NC)
Switching Principle	Slow action
Terminal Type	Connector
Utilisation Category	DC-13   AC-15
Utilisation Category AC-15	1.5 A
Utilisation Category DC-13	0.25 A

### Physical Attributes

Actuator Type	Roller lever
Enclosure Material	Aluminium
Gross Weight (g)	56.17
Maximum Ambient Temperature (°C)	60
Minimum Ambient Temperature (°C)	-25
Net Weight (g)	441
Storage Temperature (°C)	-40 to 85
Wire Cross-Section	0.5 mm

### Dimensions

Sensor Height (mm)	25
Sensor Length (mm)	46.5

### Protection & Standards

Degree of Protection	IP54
Standards	EN IEC 61496-1 / CLC/TS 61496-2

### Resources



Product catalogue (Flipbook)

[Download from here](#)

---