

Product No: ISDA073424R1

ABB E6.2H/MS 4000 3P F HR ISDA073424R1

FEATURES

- IP30 protection
- Lifting plates
- Adjustable rear terminals
- S51 250V trip indicator



General Information

Brand	ABB
Product Type	Non-automatic ACB
Suitable For	Distribution Board Installation
Type	Main Switch
Version	Fixed

Technical Attributes

Design of Control Element	Push Button
Breaking Capacity 415V AC - I _{cu} (kA)	100
Main Circuit Electrical Connection	Bolt Connection
Maximum Operational Voltage AC (V)	690
No. of Poles	3
Power Loss (W)	309
Rated Current (A)	4000
Rated Impulse Withstand Voltage (kV)	12
Rated Insulation Voltage AC (V)	1000
Rated Operational Current AC-21A 415V (A)	4000
Rated Operational Current AC-23A 380-415V (A)	4000
Rated Operational Voltage AC (V)	690
Rated Short-Time Withstand Current - I _{cw} (kA)	100
Rated Short-time Withstand Current - I _{cw} (kA/1s)	100
Rated Uninterrupted Current - I _u (A)	4000
Terminal Type	HR

Physical Attributes

Interlockable	Yes
---------------	-----

Dimensions

Dimensions (mm)	762W x 371H x 270D
-----------------	--------------------

Size of Frame	E6.2
---------------	------

Protection & Standards

Degree of Protection	IP30
----------------------	------

Standards and Approvals	IEC
-------------------------	-----