

ABB E42H4ETG40W ACB E4.2H 4P 100KA WITHDRAWABLE 4000A EKIP TOUCH LSIG

E42H4ETG40W



GENERAL INFORMATION

Brand	ABB
Product Type	Automatic
Version	Withdrawable

TECHNICAL ATTRIBUTES

Breaking Capacity 415V AC - I _{cu} (kA)	100
G (0.1 to 1 x I _n) - I ₄ (A)	400-4000
I (1.5 to 15 x I _n) - I ₃ (A)	6000-60000
L (0.4 to 1 x I _n) - I ₁ (A)	1600-4000
No. of Poles	4P
Power Loss (W)	900
Rated Current (A)	4000
Rated Impulse Withstand Voltage (kV)	12
Rated Insulation Voltage AC (V)	1000
Rated Operational Voltage AC (V)	690
Rated Short-time Withstand Current - I _{cw} (kA/1s)	85
Rated Uninterrupted Current - I _u (A)	4000
S (0.6 to 10 x I _n) - I ₂ (A)	2400-40000
Terminal Type	HR-HR
Trip Unit	EKIP Touch LSIG

DIMENSIONS

Frame Size	E4.2
------------	------

PROTECTION & STANDARDS

Standards and Approvals	IEC
-------------------------	-----

RESOURCES

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------
