

## **Product No: 225182**

## STAHL YA6S/C-D-EN-SF-A-ST-00-00-00 AUDIBLE SIGNALLING DEVICE SOUNDER IN FLAMEPROOF ENCLOSURE 225182

## **FEATURES**

- Combined signal device with Xenon horn and flashing beacon
- Flameproof enclosure suitable for hazardous areas
- Operating voltage: 230 VAC
- Current consumption: 115 mA
- Features line monitoring capability
- Maximum sound level of 110 dB(A) at 1 meter distance
- Two selectable stages for operation
- Volume control with an 18 dB(A) adjustment range
- Equipped with Xenon flash tubes for high visibility signaling

General Information	
Brand	STAHL
Series	YA6S

Technical Attributes	
Maximum Continuous Voltage DC (V)	24
Nominal Output Current (A)	0.28
Rated Maximum Operational Voltage DC (V)	24

Physical Attributes	
Maximum Temperature (°C)	70
Minimum Temperature (°C)	-60

Protection & Standards	
Degree of Protection	IP66/67
Standards and Approvals	ATEX/IEC eX

## Resources

IPD > SAFETY & HAZARDOUS AREA EQUIPMENT > HAZARDOUS AREA EQUIPMENT > HAZARDOUS AREA SIGNALLING DEVICES > IPD > SAFETY & HAZARDOUS AREA EQUIPMENT > HAZARDOUS AREA EQUIPMENT > HAZARDOUS AREA EQUIPMENT > HAZARDOUS AREA CONTROL BOXES



Product catalogue (Flipbook)

Download from here