

Product No: 267067

STAHL 6002/4128-0100-152-2220-22-8500 LINEAR LUMINAIRE WITH LED GRP 267067

FEATURES

- Linear LED luminaire suitable for hazardous areas
- Operational voltage range: 100-240 VAC or 110-250 VDC
- Power consumption: 22 W
- Light color: Neutral white
- Beam angle: 120 ° x 120 ° with diffusing glass
- Temperature operating range: -40 °C to +50 °C
- Through wiring capability up to 3x16 A
- IP rating: IP66/IP67 for dust and water resistance



General Information

Brand	STAHL
Product Type	Linear
Series	6002/4

Technical Attributes

Maximum Operational Voltage AC (V)	240
Maximum Operational Voltage DC (V)	240
Minimum Operational Voltage AC (V)	100
Minimum Operational Voltage DC (V)	100
Nominal Power (W)	22
Rated Maximum Operational Voltage AC (V)	240
Rated Maximum Operational Voltage DC (V)	240
Rated Minimum Operational Voltage AC (V)	100
Rated Minimum Operational Voltage DC (V)	100

Physical Attributes

Ambient Temperature Range (°C)	-40 to +50
Maximum Temperature (°C)	50
Minimum Temperature (°C)	-40

Mounting Type

Surface

Protection & Standards

Degree of Protection

IP66/67

Standards and Approvals

ATEX/IECEx

Resources

Product catalogue (Flipbook)

[Download from here](#)