

Product No: 942 135-006

HIRSCHMANN GREYHOUND 1040 MODULAR SWITCH WITH UP TO 28 GIGABIT PORTS, 2.5 GIGABIT FIBER UPLINK TECHNOLOGY, LAYER 3 OPTION AND REDUNDANT POWER SUPPLY. 942135006

FEATURES

- Store and Forward Switching Mode
- Fanless design
- Ethernet/Fast-Ethernet Switch

General Information

| | |
|--------------|------------|
| Brand | HIRSCHMANN |
| Product Type | Managed |

Technical Attributes

| | |
|----------------------------|---|
| Operating Voltage | 2 x 24 - 48V DC / 48 - 54V DC (PoE) |
| Port Quantity and Type | 4 x GE/2.5GE SFP, 2 x FE/GE SFP(+) 6 x FE/GE TX, 2 x 8 FE/GE |
| Power Consumption (W) | 32 (Basic unit with one power supply) |
| Power Output in BTU (IT)/h | 110 |

Physical Attributes

| | |
|------------------------------------|-------------------------|
| Mounting Type | Rack Mount |
| Operational Temperature Range (°C) | -40 to +70 |
| Relative Humidity | 5-95 % (non-condensing) |
| Storage Temperature Range (°C) | -40 to +85 |

Dimensions

| | |
|-----------------|-------------------|
| Dimensions (mm) | 444W x 44H x 354D |
| Weight (kg) | 3.6 |

Protection & Standards



Approvals

CE, FCC, EN61131, EN60950,, CuI60950

Degree of Protection

IP30

Resources

Product catalogue (Flipbook)

[Download from here](#)