

## Product No: 3AXD50000716685

## ABB ACS180 4KW 9.4A IP20 MACHINERY DRIVE W/CP ACS180-04S-09A4-4 3AXD50000716685

## **FEATURES**

- ACS180 is a versatile variable speed drive (VSD) suitable for pumps, fans, compressors, conveyors, winders, and mixers.
- Compact and robust design ensures reliability and adaptability for various applications.
- The user-friendly VSD offers excellent performance and quality at a superior value.
- Essential machinery application features are embedded in the drive for enhanced functionality.
- As part of ABB's all-compatible drives portfolio, ACS180 shares a common architecture and user interfaces, facilitating ease of use and integration.



General Information	
Brand	ABB
EAN	6438177649373
Product Type	Machinery

ApplicationDomestic & CommercialCommunication ProtocolsMODBUSInput Voltage AC (V)380 - 480Maximum Output Frequency (Hz)599Maximum Output Voltage AC (V)480No. of Analogue Inputs1No. of Analogue Outputs2No. of Digital Inputs4No. of Digital Outputs2Nominal Output Current (A)9.4Number of Other HW Interfaces1	Technical Attributes	
Input Voltage AC (V)  Maximum Output Frequency (Hz)  Maximum Output Voltage AC (V)  No. of Analogue Inputs  No. of Analogue Outputs  No. of Digital Inputs  No. of Digital Outputs  2  Nominal Output Current (A)  380 - 480  480  480  480  1  2  490  490  490  490  490  490  490	Application	Domestic & Commercial
Maximum Output Frequency (Hz) 599  Maximum Output Voltage AC (V) 480  No. of Analogue Inputs 1  No. of Analogue Outputs 2  No. of Digital Inputs 4  No. of Digital Outputs 2  Nominal Output Current (A) 9.4	Communication Protocols	MODBUS
Maximum Output Voltage AC (V)  No. of Analogue Inputs  1  No. of Analogue Outputs  2  No. of Digital Inputs  4  No. of Digital Outputs  2  Nominal Output Current (A)  480	Input Voltage AC (V)	380 - 480
No. of Analogue Inputs  No. of Analogue Outputs  2  No. of Digital Inputs  4  No. of Digital Outputs  2  Nominal Output Current (A)  9.4	Maximum Output Frequency (Hz)	599
No. of Analogue Outputs 2  No. of Digital Inputs 4  No. of Digital Outputs 2  Nominal Output Current (A) 9.4	Maximum Output Voltage AC (V)	480
No. of Digital Inputs 4  No. of Digital Outputs 2  Nominal Output Current (A) 9.4	No. of Analogue Inputs	1
No. of Digital Outputs 2  Nominal Output Current (A) 9.4	No. of Analogue Outputs	2
Nominal Output Current (A)  9.4	No. of Digital Inputs	4
<u> </u>	No. of Digital Outputs	2
Number of Other HW Interfaces 1	Nominal Output Current (A)	9.4
	Number of Other HW Interfaces	1
Number of RS-485 Interfaces 1	Number of RS-485 Interfaces	1



Relative Symmetric Net Frequency Tolerance	5%
Relative Symmetric Net Voltage Tolerance	10%

Physical Attributes	
Contains	Control Element PC Connection

Dimensions	
Dimensions (mm)	70W x 220H x 143D

Resources	
IPD Product Catalogue V17	<u>Download from here</u>