

Product No: HS5E-A4403-G

IDEC SAFETY SWITCH SPRING LOCK 3000N HS5E-A4403-G

FEATURES

- Rear unlocking button for emergency escape available. Also available
- is the rear unlocking button kit.
- A variety of circuits—dual safety circuit and four-circuit independent outputs available.
- Gold-plated contacts.
- Spring lock and solenoid lock are available.
- The head orientation can be rotated, allowing 8 different actuator entries.
- A metal entry slot ensures high durability.
- An actuator with rubber bushings alleviates the impact of actuator entry into the slot.
- The actuator retention force is 1400N minimum (GS-ET-19).
- Integral cable design minimizes wiring, preventing wiring mistakes.
- LED indicator indicates the solenoid status.
- Double insulation structure.

General Information

Brand	IDEC
Product Type	Safety Interlock Switch

Technical Attributes

Minimum Electrical Life	100000
Minimum Mechanical Life	1000000
Rated Insulation Voltage (V)	250
Rated Thermal Current - Ith (A)	2.5
Resistance to Shock (m/s ²)	100
Resistance to Vibrations	10 to 55Hz

Physical Attributes

Operating Humidity	45 to 85%
Operational Temperature Range (°C)	-25 to 50

Dimensions

Weight (g)	400
------------	-----

Protection & Standards

Degree of Protection	IP67
----------------------	------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------
