

## Product No: 238148

## STAHL 6009/542-9617-1622-71 EMERGENCY LUMINAIRE FOR FLUORESCENT LAMPS GRP 238148

## **FEATURES**

- Emergency luminaire for fluorescent lamps
- Made of Glass Reinforced Plastic (GRP)
- Operational voltage range: 220 240 VAC
- Equipped with a gas-tight NiCd battery with a capacity of 7.0 Ah
- Nominal power: 18 W
- Supports 2 lamps emitting neutral white light
- Provides 1.5 to 3 hours of emergency lighting operation
- Suitable for extreme temperatures ranging from -30 °C to +50 °C
- Through wiring capability up to max. 3x16 A



General Information	
Brand	STAHL
Product Type	Emergency
Series	6009/5

Technical Attributes	
Application	Application range (zones) - 1, 2, 21, 22
Battery Size	6V, 7.0Ah
Lamp Base	G13 lamp base
Lamp Wattage (W)	36
No. of Lamps	2
Nominal Power (W)	36
Rated Frequency (Hz)	50 - 60
Rated Maximum Operational Voltage AC (V)	240
Rated Minimum Operational Voltage AC (V)	220
Rated Operational Voltage AC (V)	220 - 240

## Physical Attributes



Ambient Temperature Range (°C)	-30 to +55
Cable Type	Finely stranded, solid
Colour	Enclosure - Light Grey (RAL 7035)
Enclosure Material	Polyester resin, Glass fibre reinforced
Lamp Type	LED
Maximum Temperature (°C)	50
Minimum Temperature (°C)	-30
Mounting Type	Surface

Dimensions	
Cable Cross Section (mm²)	4 - 6
Dimensions (mm)	183.5W x 125H x 1467D

Protection & Standards	
Certifications	IECEX, ATEX
Degree of Protection	IP67
Rated Impact Resistance	IK10
Standards and Approvals	ATEX/IEC eX

Resources	
Product catalogue (Flipbook)	Download from here