

Product No: 101060463

SCHMERSAL T 4VI0H 336-11ZUE POSITION SWITCH WITH SAFETY FUNCTION 101060463



General Information

Brand	SCHMERSAL
-------	-----------

Technical Attributes

No. of Auxiliary Contacts	1
Switching Frequency	5000/h
Actuating Element	Rod Lever
Contact Material	Silver
Maximum Actuating Speed (m/s)	2.5
Maximum Bounce Duration (ms)	2
Maximum Cable Cross Section (mm ²)	2.5
Maximum Fuse Rating	6 A gG D-fuse
Minimum Cable Cross Section (mm ²)	0.75
Minimum Mechanical Life	30000000 Operations
No. of Safety Contacts	1
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	500
Rated Operational Current AC-15 (A)	4
Rated Operational Current DC-13 (A)	4
Rated Operational Voltage AC-15 (V)	230V AC
Rated Operational Voltage DC-13 (V)	24V DC
Rated Short-circuit Current (A)	1000
Switching Element	NO Contact, NC Contact

Switching Principle	Slow Action with Overlapping Contacts
Termination	Screw Terminals M20 x 1.5
Thermal Test Current (A)	10
Utilisation Category	DC-13

Physical Attributes

Actuator Type	D - According to EN 50041
Housing Material	Plastic, glass-fibre-reinforced
Lever Material	Metal Film
Maximum Ambient Temperature (°C)	80
Minimum Ambient Temperature (°C)	-30
Rod Material	Plastic

Dimensions

Sensor Length (mm)	52
Sensor Width (mm)	40.5

Protection & Standards

Degree of Protection	IP67
Standards and Approvals	EN ISO 13849-1

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------