

Product No: DSEM2P60FM

DEHN COORD. LIGHT N. CURRENT ARRESTER TYPE 1 DEHNSECURE M FOR D.C. CIRCUITS DSEM2P60FM

FEATURES

- Modular, pluggable and coordinated two-pole lightning
- Width: 4 modules
- With remote signalling contact
- Type 1 SPD in accordance with EN 61643-11
- Spark gap technology
- Fault indication
- Energy-coordinated according to IEC 62305-4



General Information

Article No.	971226
Brand	DEHN
Product Type	Surge Protection Device

Technical Attributes

Circuit Type	MSB
Lightning Impulse Current (10/350 μ s) - Iimp (kA)	25/50
Maximum Continuous Operating Voltage MCOV DC (V)	60
No. of Poles	2P+PE
Operating State/Fault Indication	Green/Red
Response Time (ns)	≤ 100
Short-Circuit Withstand Capability - I _{sc} (kArms)	25
Signal C/O Contact	Yes
SPD Type	Type 1

Physical Attributes

Mounting Type	DIN Rail
---------------	----------

Dimensions

Dimensions (mm)	0.09W x 0.12L x 0.09D
-----------------	-----------------------

No. of Modules	4
----------------	---

Weight (kg)	0.68
-------------	------

Protection & Standards

Degree of Protection	IP20
----------------------	------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------