

# LMK 351

## Screw-in Transmitter

Ceramic Sensor

accuracy according to IEC 60770:  
standard: 0.35% FSO  
option: 0.25% FSO



### Nominal pressure

from 0 ... 40 mbar up to 0 ... 20 bar

### Output signal

2-wire: 4 ... 20 mA

3-wire: 0 ... 20 mA / 0 ... 10 V

others on request

### Product characteristics

- ▶ pressure port PVDF-version for aggressive media
- ▶ pressure port G 1 1/2" for pasty and polluted media



### Optional versions

- ▶ IS-version  
Ex ia = intrinsically safe for gases and dust
- ▶ diaphragm 99.9 % Al<sub>2</sub>O<sub>3</sub>
- ▶ customer specific versions



The screw-in transmitter LMK 351 has been designed for measuring small system pressure and level measurement in container. The LMK 351 is based on an own-developed capacitive ceramic sensor element. Usage in viscous and pasty media is possible because of the flush mounted sensor.

For the usage in aggressive media a pressure port in PVDF and the diaphragm in Al<sub>2</sub>O<sub>3</sub> 99.9 % is available. An intrinsically safe version completes the range of possibilities.

### Preferred areas of use are

-  Plant and machine engineering
-  Environmental engineering  
(water – sewage – recycling)

### Preferred used for

-  Fuel and oil
-  Viscous and pasty media



Pressure ranges																	
Nominal pressure	[bar]	0.04	0.06	0.1	0.16	0.25	0.4	0.6	1	1.6	2.5	4	6	10	16	20	
Level	[mH <sub>2</sub> O]	0.4	0.6	1	1.6	2.5	4	6	10	16	25	40	60	100	160	200	
Overpressure	[bar]	2	2	4	4	6	6	8	8	15	25	25	35	35	45	45	
Permissible vacuum	[bar]	-0.2		-0.3		-0.5			-1								
Output signal / Supply																	
Standard		2-wire: 4 ... 20 mA / V <sub>S</sub> = 9 ... 32 V <sub>DC</sub>															
Option IS-version		2-wire: 4 ... 20 mA / V <sub>S</sub> = 14 ... 28 V <sub>DC</sub>															
Option 3-wire		3-wire: 0 ... 10 V / V <sub>S</sub> = 12.5 ... 32 V <sub>DC</sub>															
Performance																	
Accuracy <sup>1</sup>		standard: ≤ ± 0.35 % FSO								option for p <sub>N</sub> ≥ 0.6 bar: ≤ ± 0.25 % FSO							
Permissible load		current 2-wire: R <sub>max</sub> = [(V <sub>S</sub> - V <sub>S min</sub> ) / 0.02 A] Ω								voltage 3-wire: R <sub>min</sub> = 10 kΩ							
Influence effects		supply: 0.05 % FSO / 10 V								load: 0.05 % FSO / kΩ							
Long term stability		≤ ± 0.1 % FSO / year at reference conditions															
Turn-on time		700 msec															
Mean measuring time		5/sec															
Response time		mean response time: ≤ 200 msec								max. response time: 380 msec							
<sup>1</sup> accuracy according to IEC 60770 - limit point adjustment (non-linearity, hysteresis, repeatability)																	
Thermal effects (offset and span)																	
Tolerance band		≤ ± 1 % FSO															
In compensated range		-20 ... 80 °C															
Permissible temperatures																	
Permissible temperatures <sup>2</sup>		medium: -40 ... 125 °C				electronics / environment: -40 ... 85 °C				storage: -40 ... 100 °C							
<sup>2</sup> for pressure port in PVDF the medium temperature is -30 ... 60 °C																	
Electrical protection																	
Short-circuit protection		permanent															
Reverse polarity protection		no damage, but also no function															
Electromagnetic compatibility		emission and immunity according to EN 61326															
Mechanical stability																	
Vibration		10 g RMS (20 ... 2000 Hz)								according to DIN EN 60068-2-6							
Shock		100 g / 1 msec								according to DIN EN 60068-2-27							
Materials (media wetted)																	
Pressure port		standard: stainless steel 1.4404 (316L)								option: PVDF							
Housing		standard: stainless steel 1.4404 (316L)								option: PVDF							
Option compact field housing		stainless steel 1.4301 (304); cable gland M12x1.5, brass, nickel plated (clamping range 2 ... 8 mm)															
Seals		FKM -40 ... 125 °C				FFKM -15 ... 125 °C				EPDM -40 ... 125 °C							
Diaphragm		standard: ceramics Al <sub>2</sub> O <sub>3</sub> 96 %								options: ceramics Al <sub>2</sub> O <sub>3</sub> 99.9 %							
Media wetted parts		pressure port, seals, diaphragm															
Explosion protection (only for 4 ... 20 mA / 2-wire)																	
Approval DX14-LMK 351		IBExU05ATEX1070 X stainless steel-pressure port with connector/cable outlet: zone 0: II 1G Ex ia IIC T4 Ga zone 20: II 1D Ex ia IIIC T110 °C Da plastic-pressure port with connector/cable outlet: zone 0/1: II 1/2G Ex ia IIC T4 Ga/Gb zone 20/21: II 1/2D Ex ia IIIC T110 °C Da/Db															
Safety technical maximum values		U <sub>i</sub> = 28 V, I <sub>i</sub> = 93 mA, P <sub>i</sub> = 660 mW, C <sub>i</sub> = 14 nF, L <sub>i</sub> ≈ 0 μH, C <sub>qnd</sub> = 27 nF															
Max. permissible temperature for environment		in zone 0: -20 ... 60 °C for p <sub>atm</sub> 0.8 bar up to 1.1 bar zone 1 and higher: -25 ... 70 °C															
Connecting cables (by factory)		cable capacity: signal line / shield also signal line / signal line: 220 pF/m				cable inductance: signal line / shield also signal line / signal line: 1.5 μH/m											
Miscellaneous																	
Current consumption		signal output current: max. 21 mA				signal output voltage: max. 5 mA											
Weight		approx. 200 g															
Installation position		any															
Operational life		100 million load cycles															
CE-conformity		EMV-directive: 2014/30/EU															
ATEX Directive		2014/34/EU															

**Wiring diagram**

2-wire-system (current)

3-wire-system (voltage)

**Pin configuration**

Electrical connection	ISO 4400	Binder 723 (5-pin)	M12x1 (4-pin)	compact field housing	cable colours (IEC 60757)
Supply +	1	3	1	IN +	WH (white)
Supply -	2	4	2	IN -	BN (brown)
Signal + (only for 3-wire)	3	1	3	OUT +	GN (green)
Shield	ground pin $\oplus$	5	4	$\oplus$	GNYE (green-yellow)

**Electrical connections (dimensions in mm)**

**standard**

ISO 4400 (IP 65)

**options**

Binder series 723 5-pin (IP 67)

M12x1

M12x1 4-pin (IP 67)

cable outlet with PVC cable (IP 67)<sup>3</sup>

cable outlet, cable with ventilation tube (IP 68)<sup>4</sup>

compact field housing (IP 67)

<sup>3</sup> standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 ... 70 °C)  
<sup>4</sup> different cable types and lengths available, permissible temperature depends on kind of cable

**Dimensions (in mm)**

G1 1/2" flush (DIN 3852) stainless steel

G1 1/2" flush (DIN 3852) PVDF<sup>5</sup>

material	A
stainless steel	approx. 3
PVDF	approx. 6

<sup>5</sup> not possible in combination with compact field housing

© 2023 BDISENSORS GmbH – The specifications given in this document represent the state of engineering at the time of publishing. We reserve the right to make modifications to the specifications and materials.

