

CA761/2



connectwell
THE RIGHT CONNECTION

Insulated Pre Assembled Shorting Links

Internal Shorting Link Assemblies consist of a Current Bar shorting Sleeves and Screws. They install easily into the center of the Terminal Block and connect to the current bar. They are available as standard 2, 3, 4 or 10 pole assemblies and are ready for immediate installation. Insulated pre assembled shorting link assemblies provide shock protection when installed on Terminal Blocks.

PRODUCT SPECIFICATION

| | |
|---------------|--------|
| Rated Current | 76 A |
| Torque | 0.8 Nm |

ORDERING INFORMATION

| CAT. NO. | DESCRIPTION | STD. PACK |
|----------|---|-----------|
| CA761/2 | Insulated Pre assembled Shorting Link for 2 way shorting | 50 |
| CA761/3 | Insulated Pre assembled Shorting Link for 3 way shorting | 50 |
| CA761/4 | Insulated Pre assembled Shorting Link for 4 way shorting | 50 |
| CA761/10 | Insulated Pre assembled Shorting Link for 10 way shorting | 10 |

SUITABLE FOR

| | |
|----------|--|
| CTS16 | 16 sq.mm Standard Feed Through Terminal Blocks |
| CTS16UV0 | 16 sq.mm Feed Through Terminal Blocks |
| CTS16U | 16 sq.mm Standard Feed Through Terminal Blocks |