

Product No: MSB801230DDG

IDE IDE55 ROLLED MILD STEEL DOUBLE DOOR WALL MOUNTED ENCLOSURE 800Hx1200Wx300Dmm GREY MSB801230DDG

FEATURES

- - Cold-rolled steel EN 10130+A1
- - Injected polyurethane sealing gasket
- - Primer coated and hardened RAL 7035 polyester paint, embossed, with UV protection
- - Substitute G with A for orange colour RAL 2008
- - Mounting plate included



General Information

Brand	IDE
Customs Tariff Number	85.38.10.00
EAN	8431044075679
ETIM 8.0	EC000261
Product End of Life	It does not require specific recycling operations.
Product Type	Wall-mounting Cabinet

Technical Attributes

Application	Industrial environments, manufacturing companies requiring a high degree of protection against dust, splashes and impacts.
Maximum Operational Voltage (V)	1000 AC / 1500 DC

Physical Attributes

Ambient Temperature Range (°C)	-25 to +60
Cable Entry (mm)	2 x (125H x 485W)
Colour	RAL 7035
Door Profiles	4
Door Type	Double
Finish	Coated with primer, and hardened polyester paint, textured, with UV protection
Installation	Surface

Lock Type	5-mm double-bit lock - One 3-point lock
Material	Cold-rolled steel EN 10130+A1
Mounting Plate	With flat mounting plate. 2-mm galvanised sheet steel
No. of Hinges	6
No. of Locks	3 points
Sealing Gasket	Injected polyurethane sealing gasket
Supply	Supplied in individual packaging containing cabinet, plate and accessory bag. Mounting plate is supplied assembled inside the cabinet.
Type of Door	Double opaque door. Reversible
Wall Fixing (mm)	760H x 960W

Dimensions

Dimensions (mm)	800H x 1200W x 300D
Mounting Plate Size (mm)	770W x 1150H
Thickness (mm)	Enclosure: 1.5 Door: 2 Cable entry lid: 2
Usable Internal Space (mm)	750H x 1150W x 279D
Weight (kg)	59.7

Protection & Standards

Certifications	UL508A
Degree of Protection	IP55
Directive	2014/35/EU
NEMA Degree of Protection	NEMA 1, 12
Rated Impact Resistance	IK10
Standards	IEC 62208, IEC 61439-1
Sustainability	RoHS - REACH

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------