

Product No: 101172761

SCHMERSAL SEPG05.3.3.1.22/95 TWO-HAND CONTROL PANEL 101172761

FEATURES

- Two-hand control panel with aluminium enclosure
- Can be assembled as a construction kit
- Designed for use with EMERGENCY-OFF applications
- Features one Emergency Stop button and two operating push buttons
- Includes two openers and two shutters
- Emergency Stop button diameter: 49 mm
- Operating push buttons diameter: 55 mm
- Equipped with screw connection terminals
- Thermal test current rated at 10 A



General Information

Brand	SCHMERSAL
Recommended Product Combination	SRB201ZH
Series	SEP

Technical Attributes

Maximum Cable Cross Section (mm ²)	1.5
Minimum Mechanical Life	10000000 Operations
No. of Normally-closed Contacts	2
No. of Normally-open Contacts	2
Rated Insulation Voltage (V)	440
Rated Operational Current AC-15 (A)	8
Rated Operational Current DC-13 (A)	5
Rated Operational Voltage AC-15 (V)	250V AC
Rated Operational Voltage DC-13 (V)	24V DC
Termination	Screw Terminals M20 x 1.5
Thermal Test Current (A)	10
Utilisation Category	DC-13

Physical Attributes

Enclosure Coating Material	Powder-coated
----------------------------	---------------

Housing Material	Aluminium
------------------	-----------

Dimensions

Depth (mm)	160
------------	-----

Height (mm)	184
-------------	-----

Width (mm)	494
------------	-----

Protection & Standards

Degree of Protection	IP65
----------------------	------

Standards and Approvals	EN IEC 60947-5-1
-------------------------	------------------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------