


Product No: OT250E03K

ABB SWITCH DISCONNECTOR 250A DIRECT HANDLE OT250E03K

FEATURES

- Base mounting
- Standards and Approvals: IEC 60947-3
- Degree of protection: IP00



General Information

Brand	ABB
Product Type	Base Mount Load Break Switch

Technical Attributes

Conventional Free-Air Thermal Current - I _{th} (A)	250
Conventional Thermal Current - I _{the} (A)	250 (Fully Enclosed)
Net Weight (kg)	1.4
No. of Poles	3
Power Loss (W)	6.5/Pole
Rated Impulse Withstand Voltage (kV)	12
Rated Insulation Voltage (V)	1000
Rated Operational Current AC-22A 380-415V (A)	250
Rated Operational Current AC-22A 500V (A)	250
Rated Operational Current AC-22A 690V (A)	250
Rated Operational Current AC-23A 380-415V (A)	250
Rated Operational Current AC-23A 690V (A)	250
Rated Operational Voltage (V)	8
Rated Voltage (V)	1000
Terminal Type	Lug terminals

Physical Attributes

Colour	Black (Handle)
--------	----------------

Handle Type	Direct mounted pistol
Mounting Type	Base mounting
Terminal Width (mm)	20

Dimensions

Dimensions (mm)	145.5W x 150H x 107D
Weight (kg)	1.4

Protection & Standards

Degree of Protection	IP00 (Front)
Pollution Degree	3
Standards and Approvals	IEC 60947-3