

Product No: CUB5COM1

RED LION PLUG-IN RS485 COMMUNICATIONS CARD CUB5COM1

FEATURES

- Current Switch with GO/NO GO feature
- Fixed current range: 0 to .75 A
- PID Controller with 1/8 DIN size
- Power connection options: AC 100 to 240 VAC
- Main control output: Relay
- Universal input compatibility including temperature and RTD
- Indication accuracy: $\pm(0.3\%$ of span, $+1\text{ }^{\circ}\text{C}$) at $25\text{ }^{\circ}\text{C}$
- Supports multiple thermocouple input types (T, E, J, K, R, S, B, N, L, U, TXK)
- Accepts RTD inputs (2 or 3 wire) with excitation of 180 mA



General Information

Brand	RED LION
Product Type	Accessory
Series	EPAX
Suitable For	CUB5 Units

Technical Attributes

Communication	RS-485
Nominal Power (W)	18
Rated Maximum Operational Voltage AC (V)	250
Rated Minimum Operational Voltage AC (V)	85

Physical Attributes

Maximum Temperature ($^{\circ}\text{C}$)	65
Minimum Temperature ($^{\circ}\text{C}$)	0
Operational Temperature Range ($^{\circ}\text{C}$)	-35 to +75

Protection & Standards

Degree of Protection

IP20

Resources

Product catalogue (Flipbook)

[Download from here](#)
