

## Product No: UB10.245

### PULS DC-UPS CONTROL UNIT 24VDC 15A UB10.245

#### FEATURES

- 24V DC-UPS with an additional 12V output for various applications
- Only one 12V battery required
- Stable output voltage in buffer mode
- Superior battery management for longest battery life
- Comprehensive diagnostic and monitoring functions
- Replace battery signal included
- Electronically overload and short circuit protected
- 50% Power reserves



#### General Information

Brand	PULS
Country of Origin	China / Czech Republic
Customs Tariff Number	85044083
E Classification	E-CS04
Product Type	DC-UPS
Range	DIMENSION
Series	U series
Warranty Period (Months)	36

#### Technical Attributes

Battery Size	12 V, 3.9 to 40 Ah
Connection Type	Spring clamps
Derating	0.25 W/°C
Derating Temperature (°C)	> +60
Efficiency	%
Input Voltage Range DC (V)	24
Internal Current Consumption (A)	1.3 (Including Charging Current)
Minimum Input Voltage DC (V)	24

Nominal Output Current 'b' (A)	10
Output Voltage (V)	24
Rated Current (A)	10
Special Application	Hazardous location
Storage Element	External lead acid battery
Temperature Tracking Of The End-of-charge Voltage	Manual-select
Use In Crosslinking	Yes

### Physical Attributes

Conformal Coating	No
Mounting Type	DIN Rail
Operational Temperature Range (°C)	-25 to 70

### Dimensions

Dimensions (mm)	49W x 124H x 117D
Weight (g)	350

### Protection & Standards

Degree of Protection	IP20
Standards and Approvals	ATEX EN 60079, Class I Div. 2 Canada - CSA, Class I Div. 2 USA - CSA, Class I Div. 2 Canada - UL, Class I Div. 2 USA - UL, EU Declaration of Conformity, IECEx IEC 60079, IEC 60950 CB Scheme, UL 508 Canada, UL 508 USA, UL 60950-1 Canada, UL 60950-1 USA, UK Declaration of Conformity

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------