

Product No: BCOML2BEHF5

DEHN MODULAR ARRESTER FOR 2 SINGLE CORES BLITZDUCTORCONNECT W. FAULT INDICATION BCOML2BEHF5

FEATURES

- Modular, pluggable combined arrester
- Tested to EN/IEC 61643-21
- Energy coordinated according to IEC 61643-22
- Width of 6 mm
- Cable connection: Push-in



General Information

Article No.	927270
Brand	DEHN
Product Type	Signal Line Protector

Technical Attributes

Connection Type	Push-in
Lightning Impulse Current (10/350 μ s) - I_{imp} (kA)	1.5 (Per Line)
Maximum Continuous Operating Voltage MCOV AC (V)	6
Maximum Continuous Operating Voltage MCOV DC (V)	8.5
Maximum Discharge Current (8/20 μ s) - I_{max} (kA)	20
Nominal Discharge Current (8/20 μ s) - I_n (kA)	5 (Per Line)
Nominal Voltage (V)	5
Operating State/Fault Indication	Green/Red
Total Discharge Current (10/350 μ s) - I_{total} (kA)	3
Total Discharge Current (8/20 μ s) - I_{total} (kA)	10
Voltage Protection Level - U_p (kV)	≤ 0.05 (Line-Line)/ ≤ 0.07 (Line-PG)

Physical Attributes

Mounting Type	DIN Rail
---------------	----------

Dimensions

Cable Cross Section (mm ²)	0.2 - 2.5 (Solid/Flexible)
Dimensions (mm)	0.08W x 0.12L x 0.01D
Module Width (mm)	6
Weight (kg)	0.06

Protection & Standards

Degree of Protection	IP20
----------------------	------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------