

## Product No: OT40F3C

### ABB OT40F3C CHANGE-OVER SWITCH OT40F3C

#### FEATURES

- Modular design, the handle and shaft can be ordered separately
- Easy front operation, enhancing accessibility and ease of use
- Open transition ensures a secure and reliable change-over process
- Versatile terminal positioning, providing flexibility in installation



#### General Information

Brand	ABB
Included	Knob Handle
Product Type	Manual
Suitable For	Distribution Board Installation
Type	Main Switch

#### Technical Attributes

Conventional Free-Air Thermal Current - I <sub>th</sub> (A)	40
Indication	I-O-II
Maximum Operational Voltage AC (V)	750
Mode of Operation	Front
No. of Poles	3
No. of Switches	1
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Power Loss (W)	1.6
Rated Impulse Withstand Voltage (kV)	8
Rated Insulation Voltage (V)	750
Rated Operational Current AC-21A 415V (A)	40
Rated Operational Current AC-22A 415V (A)	40
Rated Operational Current AC-23A 380-415V (A)	23

Rated Operational Power AC-23A 380-415V (kW)	11
Rated Operational Power AC-23A 415V (kW)	11
Rated Operational Voltage (V)	750
Rated Operational Voltage AC (V)	415
Rated Short-Time Withstand Current - I <sub>cw</sub> (kA)	0.5
Terminal Type	Screw
Transition Type	Open

### Physical Attributes

Control Element Colour	Black
Interlockable	Yes
Mounting Type	Front Mount 4-hole

### Dimensions

Cable Cross Section (mm <sup>2</sup> )	0.75 - 10
Dimensions (mm)	70W x 68H x 68D
Weight (kg)	0.25

### Protection & Standards

Degree of Protection	IP20
NEMA Degree of Protection	1
Pollution Degree	3

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------