

Product No: S301PB10NA

ABB MCB 1P 10A 15KA B CURVE S300P S301PB10NA

FEATURES

- Assures protection in industrial installations against overload and short circuits
- IEC and UL standards
- B Curve



General Information

Brand	ABB
Product Type	MCB
Series	S300P

Technical Attributes

Power Supply Connection	Arbitrary
Curve Type	B
Dielectric Test Voltage (kV)	2
Electrical Endurance (Cycles)	20000
Mechanical Endurance (Cycles)	20000
Net Weight (kg)	0.248
No. of Poles	1+NP
No. of Protected Poles	1P
Overvoltage Category	IV
Power Loss (W)	2.8
Rated Current (A)	10
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	6
Rated Insulation Voltage (V)	500
Rated Operational Voltage AC (V)	240
Terminal Type	Screw Terminals
Tightening Torque (Nm)	2.8

Trip Curve	B Curve
Voltage Type	AC/DC
Wire Stripping Length (mm)	14

Physical Attributes

Actuator Material	Insulation Group II, Black, Sealable
Ambient Temperature Range (°C)	-40 to +70 (Operation)
Housing Material	Insulation Group I, RAL 7036
Mounting Position	Any
Mounting Type	DIN Rail

Dimensions

Dimensions (mm)	35W x 88H x 69D
-----------------	-----------------

Protection & Standards

Degree of Protection	IP20, IP40 in enclosure with cover
Pollution Degree	3
Standards	CSA 22.2 No. 235, IEC/EN 60898-1, IEC/EN 60947-2, UL 1077