

**Product No: 943 940-999-015**

**HIRSCHMANN MANAGED RACKMOUNT SWITCH MAR1030-CC  
TTTTBBBBBBBBBBBBBBBBBBBBBUGGHPH 943 940-999-015**

**FEATURES**

- Ruggedized Managed Rackmount Switch
- 2 Combo Ports (2 x 10/100/1000 TX or 2 x GE SFP)
- 2 Twisted Pair RJ45 ports with 10/100 Mbit/s
- 2 Multi-mode Fiber ports with 100BASE-FX, MM-LC FE
- 20 Singlemode Fiber ports with 100 Mbit/s SC connectors
- Operating temperature range from -40 °C to +85 °C
- Dual power supply options: 110/250 V DC and 110/230 V AC (spring clip)
- Layer 2 Professional network management features

**General Information**

Brand	HIRSCHMANN
Series	MAR1030

**Technical Attributes**

No. of 100Mb Ports	24
No. of 1GB Ports	2
No. of Ethernet Ports	4
No. of Fiber Ports	22
Rated Maximum Operational Voltage AC (V)	230
Rated Maximum Operational Voltage DC (V)	250
Rated Minimum Operational Voltage AC (V)	110
Rated Minimum Operational Voltage DC (V)	110

**Physical Attributes**

Maximum Temperature (°C)	85
Minimum Temperature (°C)	-40
Mounting Type	19" Control Cabinet

### Protection & Standards

Degree of Protection	IP30
Standards and Approvals	IEC 61850-3

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------