

## Product No: 4414001111123030000

## BD SENSORS LMP308 SEPARABLE SS 4.0BAR SS316L DIAPH. 4-20MA 2WIRE FKM 0.35% ACC. PUR 35MTR 4414001111123035000

## **FEATURES**

- Diameter 35 mm.
- Cable and sensor head detachable.
- High accuracy.
- Good long term stability.

General Information	
Brand	BD SENSORS
Product Series	LMP 308
Product Type	Stainless Steel Sensor
Series	LMP 308
Version	Standard

Technical Attributes	
Accuracy	Standard for pN ≥ 0.4 bar: 0.35 % FSO
Application	Preferred areas of use are Water/ Filtrated sewage Ground water level measurement. Level measurement in wells and open waters. Rain spillway basin. Level measurement in container. Water treatment plants. Water recycling.
Electrical Connection	PUR-cable (black, Ø 7.4 mm)) [Cable with integrated ventilation tube for atmospheric pressure reference]
Electrical Protection	Short-circuit protection: Permanent, Reverse polarity protection: No damage, but also no function, Lightning protection: Integrated, Electromagnetic compatibility: emission and immunity according to EN 61326.
Output Signal	4 20 mA / 2-wire
Permissible Temperatures	Medium: -20 70 °C Storage: -25 70 °C
Pressure (mH <sub>2</sub> O)	40



Response Time (ms)	≤ 10
Seals	FKM

Physical Attributes	
Diaphragm Material	Stainless steel 1.4435 (316L)
Housing Material	Stainless steel 1.4404 (316L)

Dimensions	
Cable Length (m)	30

Resources	
Product catalogue (Flipbook)	<u>Download from here</u>