

Product No: DS201C20A30

ABB RCBO, 6kA 1P+N 20A C-CURVE 30mA DS201C20A30

FEATURES

- - Protection against short circuit, thermal overload and earth leakage
- - Contact Position Indication (CPI)
- - Earth fault indicator to identify easier earth faults
- - Test pushbutton to verify the correct functioning of the device
- - Laser printed data for quick identification
- - Finger safety with IP20 terminals
- - Pole configuration 1P+N



General Information

Brand	ABB
Product Type	RCBO
Series	DS200

Technical Attributes

Breaking Capacity 240V AC - I _{cu} (kA)	6
Curve Type	C Curve
No. of Poles	1P+N
Rated Current (A)	20
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage AC (V)	500
Rated Operational Voltage AC (V)	230/240
Rated Residual Current (mA)	30
Rated Voltage (V)	230
Terminal Type	Screw Terminals
Type of Residual Current	A

Physical Attributes

Operational Temperature Range (°C)	-25 to +55
------------------------------------	------------

Dimensions

Dimensions (mm)	35Wx85Hx69D
-----------------	-------------

Protection & Standards

Degree of Protection	IP40 (Housing), IP20 (Terminals)
----------------------	----------------------------------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------
