

Product No: BCOMODML2BEHF5

DEHN PROTECTION MODULE FOR 2 SINGLE CORES BLITZDUCTORCONNECT W. FAULT INDICATION BCOMODML2BEHF5

FEATURES

- Pluggable combined arrester module
- Tested to EN/IEC 61643-21
- Energy coordinated according to IEC 61643-22
- Width of 6 mm
- Replacement module



General Information

Article No.	927070
Brand	DEHN
Product Type	Signal Line Protector

Technical Attributes

Lightning Impulse Current (10/350 μ s) - Iimp (kA)	1.5 (Per Line)
Maximum Continuous Operating Voltage MCOV AC (V)	6
Maximum Continuous Operating Voltage MCOV DC (V)	8.5
Maximum Discharge Current (8/20 μ s) - I _{max} (kA)	20
Nominal Discharge Current (8/20 μ s) - I _n (kA)	5 (Per Line)
Nominal Voltage (V)	5
Operating State/Fault Indication	Green/Red
Total Discharge Current (10/350 μ s) - I _{total} (kA)	3
Total Discharge Current (8/20 μ s) - I _{total} (kA)	10
Voltage Protection Level - U _p (kV)	≤ 0.05 (Line-Line)/ ≤ 0.07 (Line-PG)

Physical Attributes

Pluggable	Plugs in to BCO Base Part
-----------	---------------------------

Dimensions

Dimensions (mm)	0.08W x 0.12L x 0.01D
-----------------	-----------------------

Module Width (mm)	6
-------------------	---

Weight (kg)	0.04
-------------	------

Protection & Standards

Degree of Protection	IP20
----------------------	------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------