

## Product No: PSR30-600-11

### ABB PSR30-600-11 SOFTSTARTER - 30 A - 208 ... 600 V AC PSR30-600-11

#### FEATURES

- Most compact softstarters with basic functionality and values
- Two-phase controlled
- Soft start and stop with voltage ramp
- Built-in bypass for energy saving and easy installation
- Easy set-up by three potentiometers
- Run and Tor of Ramp relays available for monitoring
- Connection kits available for connection to ABB's manual motor starters (MMS)
- Fieldbus communication with fieldbus plug adapter and fieldbus plug
- Rated control supply voltage: 24 VAC/DC



#### General Information

Brand	ABB
Product Type	Compact - PSR

#### Technical Attributes

Actuating Voltage Type	AC/DC
Display Screen	No
IEC Rated Operational Power 400V - Normal (kW)	15
Rated Control Supply Voltage AC/DC (V)	24
Rated Control Supply Voltage AC (V)	24
Rated Control Supply Voltage DC (V)	24
Rated Current - Medium Duty (A)	30
Rated Operational Current (A)	30
Rated Operational Power - In-Line Connection (230V) (kW)	7.5
Rated Operational Power - In-Line Connection (400V) (kW)	15
Rated Operational Voltage AC (V)	208
Rated Supply Voltage AC (V)	24
Release Class	Adjustable

### Physical Attributes

Operational Temperature Range (°C)	-25 to +60
------------------------------------	------------

### Dimensions

Dimensions (mm)	128W x 160H x 45D
-----------------	-------------------

Size of Frame	B
---------------	---

### Protection & Standards

Degree of Protection	IP20
----------------------	------

NEMA Degree of Protection	1
---------------------------	---