

## ABB DS203NCC32A30 RCBO 6kA 3P+N 32A C CURVE TYPE A 30mA

DS203NCC32A30

### FEATURES

- Protection against short circuit, thermal overload and earth leakage
- Contact Position Indication (CPI)
- Earth fault indicator to identify easier earth faults
- Test pushbutton to verify the correct functioning of the device
- Laser printed data for quick identification
- Finger safety with IP20 terminals
- Pole configuration 3P+N



### GENERAL INFORMATION

Brand	ABB
Product Type	RCBO
Series	DS203NC

### TECHNICAL ATTRIBUTES

Application	Commercial and Industrial
Breaking Capacity 230V AC - Icu (kA)	10
Curve Type	C Curve
No. of Poles	3P+N
Power Loss (W)	15.1
Rated Conditional Short-Circuit Current - Inc (kA)	10
Rated Current (A)	32
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage AC (V)	500
Rated Operational Voltage AC (V)	400/415
Rated Residual Current (mA)	30
Rated Short-Circuit Capacity - Icn (kA)	6
Rated Voltage AC (V)	230/400
Type of Residual Current	A

### PHYSICAL ATTRIBUTES

Housing Material	Insulation Group II, RAL 7035
------------------	-------------------------------

**PHYSICAL ATTRIBUTES**

Mounting Type	DIN Rail
---------------	----------

**PROTECTION & STANDARDS**

Degree of Protection	IP20
----------------------	------

Pollution Degree	2
------------------	---

**RESOURCES**

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------