

## Product No: DS203NCC32A30

### ABB DS203NCC32A30 RCBO 6kA 3P+N 32A C CURVE TYPE A 30mA

#### FEATURES

- - Protection against short circuit, thermal overload and earth leakage
- - Contact Position Indication (CPI)
- - Earth fault indicator to identify easier earth faults
- - Test pushbutton to verify the correct functioning of the device
- - Laser printed data for quick identification
- - Finger safety with IP20 terminals
- - Pole configuration 3P+N



#### General Information

Brand	ABB
Product Type	RCBO
Series	DS203NC

#### Technical Attributes

Application	Commercial and Industrial
Breaking Capacity 230V AC - I <sub>cu</sub> (kA)	10
Curve Type	C Curve
No. of Poles	3P+N
Power Loss (W)	15.1
Rated Conditional Short-Circuit Current - I <sub>nc</sub> (kA)	10
Rated Current (A)	32
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage AC (V)	500
Rated Operational Voltage AC (V)	400/415
Rated Residual Current (mA)	30
Rated Short-Circuit Capacity - I <sub>cn</sub> (kA)	6
Rated Voltage AC (V)	230/400

Type of Residual Current	A
--------------------------	---

---

### Physical Attributes

Housing Material	Insulation Group II, RAL 7035
Mounting Type	DIN Rail

---

### Protection & Standards

Degree of Protection	IP20
Pollution Degree	2

---

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------

---