

Product No: MS132-20LC

ABB MS132-20LC LAMP CIRCUIT BREAKER 16 ... 20 A MS132-20LC



General Information

Brand	ABB
Product Type	Accessory
Series	MS132

Technical Attributes

Design of Control Element	Turn Button
Breaking Capacity 230V AC - I _{cu} (kA)	50
Breaking Capacity 400V AC - I _{cu} (kA)	50
Current Setting Range (A)	16 - 20
Indication	On/Off/Trip
Main Circuit Electrical Connection	Screw Connection
No. of Poles	3
Overload Release Current Setting (A)	16
Phase Failure Sensitive	Yes
Rated Instantaneous Short-Circuit Current - I _i (A)	150
Rated Insulation Voltage (V)	690
Rated Operational Current (A)	20
Rated Operational Voltage AC (V)	400
Rated Uninterrupted Current - I _u (A)	20
Switching Type	Thermomagnetic
Terminal Type	Screw terminals
Thermal Overload Protection	Yes

Physical Attributes

Actuator Type	Rotary Handle
---------------	---------------

Operational Temperature Range (°C)	-25 to +70
------------------------------------	------------

Storage Temperature (°C)	-50 to +80
--------------------------	------------

Dimensions

Dimensions (mm)	45W x 97.8H x 86.55D
-----------------	----------------------

Protection & Standards

Degree of Protection	IP20
----------------------	------

Pollution Degree	3
------------------	---

Standards and Approvals	IEC/EN 60947-1, IEC/EN 60947-2
-------------------------	--------------------------------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------