

PRODUCT-DETAILS

WA4-11 WA4-11 24-60V50/60HZ-DC Mechanical Latching Unit



General Information	
Extended Product Type	WA4-11
Product ID	1SBN040100R1011
EAN	3471523131064
Catalog Description	WA4-11 24-60V50/60HZ-DC Mechanical Latching Unit
Long Description	WA4-11 is a mechanical latching unit for AF09(Z) AF65 contactors and NF(Z) contactor relays ensuring that the contactor or contactor relay remains switched on even if there is a lack or a failure of voltage, in application such as energy conservation. Standard contactors can be easily converted into compact latched contactors. The WA4 block contains a mechanical latching device with electromagnetic impulse unlatching (AC or DC) or manual unlatching Select quickly the WA4 coil thanks to an unlimited choice of control voltages (e.g. 24, 28, 32, 36, 42, 48, 50, 55, 60 V 50/60 Hz - DC) included inside a large range of voltages from 24 to 60 V 50/60 Hz - DC • Extend your auxiliary control circuit by adding additional 1-pole front mounted CA4 and 2-pole side mounted CAL4 auxiliary contact blocks • Design easily your installation with 25% less depth required in panel mounting • Reduce your stock and increase your solution proposal with 50% of less variants required compared to conventional solutions

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85389099

WA4-11 2

Product Main Type Accessories for Block Contactors Popular Downloads 1SBC101046M6801 Instructions and Manuals 2CDC001079B0201 **CAD Dimensional** Drawing **Dimensions** Product Net Width 19.8 mm 67.4 mm Product Net Depth / Length Product Net Height 41 mm 0.065 kg Product Net Weight Technical Coil Consumption Pull-in DC (Umin / Umax) 15 ... 100 W **Connecting Capacity** Flexible with Ferrule 1/2x 0.75 ... 2.5 mm² Control Circuit Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm² Rigid Solid 1/2x 1 ... 2.5 mm² Rigid Stranded 1/2x 1 ... 2.5 mm² Rated Control Circuit 50 Hz 24 ... 60 V Voltage (U_c) 60 Hz 24 ... 60 V DC Operation 24 ... 60 V Rated Frequency (f) Control Circuit 50 / 60 Hz acc. to IEC 60947-5-1 690 V Rated Insulation Voltage IEC/EN 60947-4-1, UL 60947-1, UL 60947-4-1, CSA C22.2 No. 60947-1-13, Standards CSA C22.2 No. 60947-4-1-14 Suitable For AF09 AF09Z AF12 AF12Z AF16 AF16Z AF26 AF26Z AF30 AF30Z AF38 AF38Z AF40 AF52 AF65 NF22E NFZ22E NF31E NFZ31E NF40E NFZ40E

Terminal Type

Tightening Torque

Wire Stripping Length

Screw Terminals

Control Circuit 1.2 N·m

Control Circuit 10 mm

WA4-11 3

Technical UL/CSA	
Tightening Torque UL/CSA	Control Circuit 11 in·lt
Environmental	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Maximum Operating Altitude Permissible	Without Derating 3000 m
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
Certificates and Declarations	
CB Certificate	CB_HU-002678-A1
CCC Certificate	CCC_2018010303063035
CQC Certificate	CQC2018010303063035
Declaration of Conformity - CCC	2020980303000186
Declaration of Conformity - CE	1SBD250020U1000
Declaration of Conformity - UKCA	1SBD250042U1000
EAC Certificate	EAC_RU C-FR ME77 B02940
UL Certificate	UL_20181026-E312527_7_2
UL Listing Card	UL_E312527
Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	72 mm
Package Level 1 Depth / Length	25 mm
Package Level 1 Height	44 mm
Package Level 1 Gross Weight	0.08 kg
Package Level 1 EAN	3471523131064
Classifications	
eClass	V11.1 : 27371392

ETIM 6

EC002498 - Accessories for low-voltage switch technology

WA4-11 4

ETIM 7	EC002498 - Accessories for low-voltage switch technology
ETIM 8	EC002498 - Accessories/spare parts for low-voltage switch technology
ETIM 9	EC002498 - Accessories/spare parts for low-voltage switch technology
IDEA Granular Category Code (IGCC)	5219 >> Switch part or accessory
UNSPSC	39122221

Categories

 $\text{Low Voltage Products and Systems} \rightarrow \text{Control Products} \rightarrow \text{Contactors} \rightarrow \text{Block Contactors Accessories}$

