

Product No: DPICDEXI24N

DEHN DPICDEXI24N SPD T2 FOR SIGNALS AND MEASUREMENT EQUIP.

FEATURES

- - Use in intrinsically safe measuring circuits & bus systems
- - Self-capacitance & self-inductance negligibly small
- - Meets FISCO requirements
- - Easy to mount
- - Standards IEC/EN 61643-21
- - ATEX, IECEx, CCC, CSA Approved



General Information

Article No.	929963
Brand	DEHN
Product Type	Signal Line Protector

Technical Attributes

Lightning Impulse Current (10/350 μ s) - Iimp (kA)	1 (Line-PG)
Maximum Continuous Operating Voltage MCOV AC (V)	22.6
Maximum Continuous Operating Voltage MCOV DC (V)	32
Nominal Discharge Current (8/20 μ s) - In (kA)	0.15 (Line-Line)/10 (Line-PG)
Nominal Voltage (V)	24
Thread Size	1/2 - 14 NPT Male
Total Discharge Current (8/20 μ s) - Itotal (kA)	10
Voltage Protection Level - Up (kV)	≤ 0.058 (Line-Line)/ ≤ 1.7 (Line-PG)

Physical Attributes

Enclosure Material	Stainless steel (V4A)
--------------------	-----------------------

Protection & Standards

Degree of Protection	IP67
----------------------	------

Resources

Product catalogue (Flipbook)

[Download from here](#)
