

Product No: VB7300101

ABB VB7-30-01-01 MINI REVERSING CONTACTOR 24 V AC - 3 NO - 0 NC - SCREW TERMINALS VB7300101

FEATURES

- Very compact, falt design
- Easy and quick mounting in any position
- Compact reversing contactor as one module, including blocking function
- Low power consumption
- Positive linked and guided contacts
- Hum-free operating DC coil



General Information

| | |
|--------------|----------------|
| Brand | ABB |
| Product Type | Mini Contactor |

Technical Attributes

| | |
|---|---------------------|
| Actuating Voltage Type | AC |
| Auxiliary Contacts | 1NC |
| Function | Reversing Contactor |
| Main Circuit Electrical Connection | Screw Connection |
| No. of Normally-closed Auxiliary Contacts | 1 |
| No. of Normally-open Contacts | 3 |
| No. of Poles | 3 |
| Operating Voltage AC (V) | 690 |
| Power Loss (W) | 2.0/pole |
| Rated Control Circuit Voltage AC (V) | 24 |
| Rated Control Supply Voltage AC (V) | 24 |
| Rated Frequency (Hz) | 50/60 |
| Rated Impulse Withstand Voltage (kV) | 6 |
| Rated Insulation Voltage (V) | 690 |
| Rated Operational Current AC-1 240V (A) | 20 |
| Rated Operational Current AC-1 690V (A) | 6 |

| | |
|--|-------|
| Rated Operational Power AC-3 415V (kW) | 5.5 |
| Rated Operational Voltage AC (V) | 690 |
| Rated Supply Voltage AC (V) | 24 |
| Terminal Type | Screw |

Physical Attributes

| | |
|------------------------------------|------------|
| Mounting Type | Rail Mount |
| Operational Temperature Range (°C) | -20 to +55 |

Dimensions

| | |
|-----------------|-----------------------|
| Dimensions (mm) | 96.2W x 57.5H x 46.7D |
|-----------------|-----------------------|

Protection & Standards

| | |
|---------------------------|------|
| Degree of Protection | IP20 |
| NEMA Degree of Protection | 1 |
| Pollution Degree | 3 |

Resources

| | |
|------------------------------|------------------------------------|
| Product catalogue (Flipbook) | Download from here |
|------------------------------|------------------------------------|