

## **Product No: OT1000E03P**

## ABB OT1000E03P SWITCH-DISCONNECTOR OT1000E03P

## **FEATURES**

- Front operated, 3 pole switch disconnector
- Mechanism is at left end of the switch
- Base mounted
- With black handle and shaft
- Terminal bolt kit included
- Degree of protection: Handle IP65/ Front IP00



General Information	
Brand	ABB
Product Type	Base Mount Load Break Switch
Suitable For	Distribution Board Installation
Туре	Main Switch

ection
ated
n at the End of the Switch 03 (Left Side)



Technical Attributes	
Rated Operational Power AC-23A 400-415 V (kW)	560
Rated Operational Power AC-23A 500V (kW)	710
Rated Operational Power AC-23A 690V (kW)	1000
Rated Operational Voltage (V)	1000
Rated Short-Time Withstand Current - Icw (kA)	50
Rated Short-time Withstand Current - Icw (kA/ls)	50
Rated Uninterrupted Current - Iu (A)	1000
Terminal Type	Lug terminals

Physical Attributes	
Control Element Colour	Black
Handle Colour	Black
Handle Dimensions (mm)	308.7W x 70H x 69.4D
Handle Material	Plastic
Handle Type	Pistol
Included	Handle, Shaft
Interlockable	Yes
Mounting Type	Base Mount
Shaft Dimensions (mm)	12W x 12H x 280D
Terminal Width (mm)	50

Dimensions	
Cable Cross Section (mm²)	2 x 300
Dimensions (mm)	334.5W x 306H x 167D
Handle Length (mm)	274

Protection & Standards	
Degree of Protection - Handle	IP65
NEMA Degree of Protection	1
Pollution Degree	3
Standards and Approvals	IEC 60947-3

Resources	
Product catalogue (Flipbook)	Download from here