


CA514/8-2



connectwell
THE RIGHT CONNECTION

Insulated Ring Type Shorting Link

These links have a possibility of quick insertion and removal. The entire nut assembly of the Terminal Block need not be removed for the insertion or removal of these links. They are available in standard 2, 3 or 4 pole configurations. They are also available in an insulated version which provides shock protection when installed on Terminal Blocks.

PRODUCT SPECIFICATION

| | |
|---------------|--------|
| Rated Current | 125 A |
| Torque | 1.2 Nm |

ORDERING INFORMATION

| CAT. NO. | DESCRIPTION | STD. PACK |
|-----------|---|-----------|
| CA514/8-2 | Insulated Ring Type Shorting Link available in 2 Pole | 100 |
| CA514/8-3 | Insulated Ring Type Shorting Link available in 3 Pole | 50 |
| CA514/8-4 | Insulated Ring Type Shorting Link available in 4 Pole | 50 |

SUITABLE FOR

| | |
|-----------|--|
| CSTSN6USH | Nut driver operated M6 sized Stud Type Hinge Terminal Blocks, with Universal Mounting Possibility. |
| CSTSN6UE | Nut driver operated M6 sized Stud Type Terminal Blocks, with Universal Mounting Possibility. |
| CSTSN6 | M6 sized Stud Type Terminal Blocks, suitable for operation with nut driver. |
| CSTSN6U | Nut driver operated M6 sized Stud Type Terminal Blocks, with Universal Mounting Possibility. |