

ABB F202B25/0ABB03 RCCB 10kA 1P+N 25A Type B 30mA INDUSTRIAL

F202B25/0.03

FEATURES

- Protection for people and buildings against earth leakage faults
- Used where earth fault waveform may be sinusoidal or pulsating DC
- Test button for checking the correct function of the device
- Bidirectional cylindrical clamps assist and increase safety during connecting procedures
- Contact Position Indication (CPI)
- Laser printed data for quick identification
- Pole configuration 1P+N



GENERAL INFORMATION

Brand	ABB
Product Type	RCCB
Series	F200

TECHNICAL ATTRIBUTES

Application	Commercial and Industrial
No. of Poles	2P
Power Loss (W)	1.58
Rated Conditional Short-Circuit Current - Inc (kA)	10
Rated Current (A)	25
Rated Frequency (Hz)	50/60
Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage AC (V)	440
Rated Operational Voltage AC (V)	230
Rated Residual Current (mA)	30
Rated Short-Circuit Capacity - Icn (kA)	10
Rated Voltage AC (V)	230/400
Test Voltage (kV)	0.17-0.253
Type of Residual Current	B

PHYSICAL ATTRIBUTES

Mounting Type	DIN Rail
---------------	----------

PROTECTION & STANDARDS

Degree of Protection	IP40 (Housing), IP20 (Terminals)
Pollution Degree	3

RESOURCES

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------