

Product No: DSHTT2P255

DEHN 2P T1&2 12.5kA 10/350USEC 255VAC 2W+EA MONOBLOCK SHIELD DSHTT2P255

FEATURES

- Application-optimised and prewired type 1 and type 2 spark-gap-based combined lightning current and surge arrester
- Compact design due to space-saving spark gap technology with only 1 module / pole
- For use in residential buildings and special applications
- Capable of protecting terminal equipment
- For protecting low-voltage consumer's installations against surges, even in case of direct lightning strikes
- For installation in conformity with the lightning protection zone concept at the boundaries from OA " 3



General Information

Brand	DEHN
Product Type	Surge Protection Device
Reference No.	941110
Suitable For	Power Supply Systems

Technical Attributes

Follow Current Extinguishing Capability AC (kArms)	25
Lightning Impulse Current (10/350 μ s) - Iimp (kA)	25
Maximum Continuous Voltage AC (V)	255
No. of Poles	2
Nominal Voltage AC (V)	230

Physical Attributes

Enclosure Material	Thermoplastic
--------------------	---------------

Dimensions

Dimensions (mm)	72W x 90H x 36D
Weight (g)	291
Weight (kg)	0.275

Protection & Standards

Degree of Protection	IP20
Standards and Approvals	EN 61643-11

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------