

Product No: CP5.481

PULS DIN RAIL POWER SUPPLY 1 PHASE 48VDC 2.5A 120W CP5.481

FEATURES

- AC 100–240V Wide-range input
- Width only 32mm
- Efficiency up to 93.5%
- Excellent partial load efficiency
- 20% output power reserves
- Easy fuse breaking – 3 times nominal current for 12 ms
- Safe HiccupPLUS overload mode
- Active power factor correction (PFC)
- Minimal inrush current surge
- Full power between -25°C and +60°C
- DC-OK relay contact



General Information

Brand	PULS
Country of Origin	China / Czech Republic
Customs Tariff Number	85044083
E Classification	E-CS01
Product Type	Single-Phase
Range	DIMENSION
Series	C series
Warranty Period (Months)	36

Technical Attributes

Efficiency	93.50%
AC Input Type	Wide-range
Connection Type	Screw terminals
DC-OK Signal	Yes
Derating	1.6 W/°C
Derating Temperature (°C)	+45 to +60
External Input Fuse Recommendation	B-6 A / C-6 A

Hold Up Time (ms)	35
Input Inrush Current (A)	4 / 4
Input Inrush Current Limitation	NTC
Input Voltage Range AC (V)	100-240
Input Voltage Range DC (V)	110-150
Integrated Decoupling Function	No
Maximum Input Voltage DC (V)	150
Maximum Ripple and Noise Voltage (mVpp)	50
Minimum Input Voltage DC (V)	110
Output Current Range (A)	2.5 - 2.1
Output Power (W)	120
Output Voltage (V)	48-56
Power Factor	0.91
Power Loss (W)	8.4
Power Reserve Type	Power Boost
Power Reserves	20%
Rated Current (A)	2.5
Special Application	Hazardous location
Use In Crosslinking	Yes

Physical Attributes

Conformal Coating	No
Mounting Type	DIN Rail
Operational Temperature Range (°C)	-25 to 70

Dimensions

Dimensions (mm)	32W x 124H x 102D
Weight (g)	440

Protection & Standards

Degree of Protection	IP20
----------------------	------

IEC 60079, IEC 61010-2-201 CB Scheme, IEC 62368-1 CB Scheme, UL 61010-2-201 Canada, UL 61010-2-201 USA, UK Declaration of Conformity

Resources

Product catalogue (Flipbook)

[Download from here](#)
