

Product No: RSSAN-90A

IDEC RELAY SOLID STATE, 90A, INPUT 90-280V AC. OUTPUT 48-660V AC SURFACE MOUNT RSSAN-90A

FEATURES

- Input status LED Indicator
- Dual SCR output with epoxy free design
- Direct bond copper substrate with direct output lead frame termination
- Internal transient protection – built-in snubber
- EMC compliant (level 3)
- 1200 Volt blocking voltage
- 4000 Volt optical isolation
- Zero crossing voltage turn-on
- High surge capability
- Optional finger safe cover (RSS-CVR)

General Information

| | |
|--------------|-------------|
| Brand | IDEC |
| Product Type | Solid State |

Technical Attributes

| | |
|----------------------|----------|
| Input Voltage AC (V) | 90 - 280 |
| Output Current (A) | 90 |
| Rated Frequency (Hz) | 47 - 440 |

Physical Attributes

| | |
|------------------------------------|-----------|
| Operational Temperature Range (°C) | -20 to 80 |
|------------------------------------|-----------|

Dimensions

| | |
|------------|----|
| Weight (g) | 82 |
|------------|----|

Resources

| | |
|------------------------------|------------------------------------|
| Product catalogue (Flipbook) | Download from here |
|------------------------------|------------------------------------|