

Product No: 7662500152E142020000

BD SENSORS LMK458 PROBE FOR MA RINE AND OFFSHORE LMK458 PROBE FOR MARINE AND OF 7662500152E142020000

FEATURES

- Diameter 39.5 mm.
- High overpressure resistance.
- High long-term stability.
- LR, DNV, ABS & CCS certified.

General Information	
Brand	BD SENSORS
Product Series	LMK 458
Product Type	Ceramic Sensor
Version	Standard

Technical Attributes	
Accuracy	0.25 % FSO
Application	Drinking water abstraction. Desalinization plant. Shipbuilding / Offshore ballast tanks. Monitoring of a ship's position and draught. Level measurement in ballast and storage tanks.
Electrical Connection	TPE-U-cable (blue, Ø 7.4 mm) [Shielded cable with integrated ventilation tube for atmospheric reference]
Electrical Protection	Short-circuit protection: Permanent, Reverse polarity protection: No damage, but also no function, Electromagnetic compatibility: emission and immunity according to EN 61326 & DNV (Det Norske Veritas).
Mechanical Stability	4 g (according to DNV: class B, curve 2 / basis: DIN EN 60068-2-6)
Output Signal	Intrinsic safety 4 20 mA / 2-wire
Permissible Temperatures	Medium / Electronics / Environment: -25 125 °C, Storage: -40 125 °C
Pressure (mH ₂ O)	2.5



Max. respo	nse	time:	380
------------	-----	-------	-----

Seals FKM

Physical Attributes	
Design	Screw-in version
Diaphragm Material	Ceramics Al2O3 96 %
Housing Material	Stainless steel 1.4404 (316L)

Dimensions	
Cable Length (m)	20

Resources	
Product catalogue (Flipbook)	Download from here