

Product No: 101172760

SCHMERSAL SEPG05.3.1.0.22/95 TWO-HAND CONTROL PANEL 101172760

FEATURES

- Position switch with thermoplastic enclosure
- Actuating element: Angle roller lever
- Switching elements include 1 NO (Normally Open) contact and 1 NC (Normally Closed) contact
- Thermal test current: 10 A
- Utilisation category AC-15: Rated for 230 VAC at 4 A
- Utilisation category DC-13: Rated for 24 VDC at 4 A
- IP Rating: IP67 for dust and water resistance



General Information

Brand	SCHMERSAL
Recommended Product Combination	SRB201ZH
Series	SEP

Technical Attributes

Maximum Cable Cross Section (mm ²)	1.5
Minimum Mechanical Life	10000000 Operations
No. of Normally-closed Contacts	2
No. of Normally-open Contacts	2
Rated Insulation Voltage (V)	440
Rated Operational Current AC-15 (A)	8
Rated Operational Current DC-13 (A)	5
Rated Operational Voltage AC-15 (V)	250V AC
Rated Operational Voltage DC-13 (V)	24V DC
Termination	Screw Terminals M20 x 1.5
Thermal Test Current (A)	10
Utilisation Category	DC-13

Physical Attributes

Enclosure Coating Material	Powder-coated
----------------------------	---------------

Housing Material	Aluminium
------------------	-----------

Dimensions

Depth (mm)	160
Height (mm)	184
Width (mm)	494

Protection & Standards

Degree of Protection	IP65
Standards and Approvals	EN IEC 60947-5-1

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------
