

Product No: **MST301590G**

IDE IDE66 MILD STEEL TERMINAL BOX WITH PLAIN SIDES & SCREW-ON COVER 300Hx150Wx90Dmm MST301590G

FEATURES

- - Cold-rolled steel EN 10130+A1
- - Injected polyurethane sealing gasket
- - Coated with hardened RAL 7035 polyester paint, embossed, with UV protection
- - Mounting plate not included
- - According to low tension directive 2014/35/EU
- - Complies with: UNE-EN 62208
- - UL Certificate UL508A



General Information	
Brand	IDE
Customs Tariff Number	85.38.10.00
EAN	8431044016665
ETIM 8.0	EC002713
Product End of Life	It does not require specific recycling operations.
Product Type	Steel terminal box with plain sides

Technical Attributes	
Application	Industrial environments, manufacturing companies requiring a high degree of protection against dust, splashes and impacts.
Maximum Operational Voltage (V)	1000 AC / 1500 DC

Physical Attributes	
Ambient Temperature Range (°C)	-25 to +60
Colour	RAL 7035
Finish	Coated with hardened polyester paint, textured, with UV protection
Installation	Surface
Lock Type	Lid fastened with fast jackscrew with watertight caps



Mounting Plate	Without mounting plate. 2 side brackets
Sealing Gasket	Injected polyurethane sealing gasket
Supply	The body, cover and accessory bag are supplied shrink-wrapped.
Type of Door	Opaque lid
Wall Fixing (mm)	260H x 110W

Dimensions

Dimensions (mm)	300H x 150W x 90D
Thickness (mm)	1.2
Usable Internal Space (mm)	275H x 125W
Weight (kg)	2.1

Protection & Standards

Certifications	UL508A
Degree of Protection	IP66
Directive	2014/35/EU
NEMA Degree of Protection	NEMA 1, 4, 12
Rated Impact Resistance	IK10
Standards	IEC 62208
Sustainability	RoHS – REACH

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------