

## Product No:101150060

### SCHMERSAL AZM 170SK-02ZKA 24VAC/DCSOLENOID INTERLOCK 101150060



#### General Information

Brand	SCHMERSAL
-------	-----------

#### Technical Attributes

No. of Auxiliary Contacts	1
Switching Frequency	1000/h
Contact Material	Silver
Holding Force (N)	1000
Latching Force (N)	5
Maximum Actuating Speed (m/s)	2
Maximum Cable Cross Section (mm <sup>2</sup> )	1.5
Maximum Fuse Rating	6 A gG D-fuse
Maximum Holding Force (N)	1300
Maximum Storage Temperature (°C)	85
Minimum Cable Cross Section (mm <sup>2</sup> )	0.25
Minimum Mechanical Life	1000000 Operations
Minimum Positive Break Force (N)	17
Minimum Storage Temperature (°C)	25
No. of Actuating Directions	2
No. of Safety Contacts	2
Positive Break Travel (mm)	11
Power Consumption (W)	12
Rated Control Voltage AC/DC (V)	24

Rated Impulse Withstand Voltage (kV)	4
Rated Insulation Voltage (V)	250
Rated Operational Current AC-15 (A)	Safety Contacts - 4A
Rated Operational Current DC-13 (A)	Safety Contacts - 2.5A
Rated Short-circuit Current (A)	1000
Switching Element	Opener (NC)
Switching Principle	Slow Action
Termination	Screw Terminals
Thermal Test Current (A)	6

### Physical Attributes

Housing Material	Plastic, Glass-fibre Reinforced Thermoplastic, Self-extinguishing
Maximum Ambient Temperature (°C)	60
Minimum Ambient Temperature (°C)	-25

### Dimensions

Sensor Height (mm)	84
Sensor Length (mm)	30
Sensor Width (mm)	90

### Protection & Standards

Degree of Protection	IP67
Standards and Approvals	EN IEC 60947-5-1, EN ISO 13849-1

### Resources

Product catalogue (Flipbook)	<a href="#">Download from here</a>
------------------------------	------------------------------------