

Product No: ISDA071036R1

ABB E2.2N 2000 EKIP TOUCH LSIG 3P F HR ISDA071036R1

FEATURES

- IP30 protection for fixed parts
- Lifting plates
- Adjustable rear terminals
- Racked-out mechanism lock, anti-insertion lock, standard shutter lock
- Lever for racking in/out
- AUX 4Q 400V Open-Closed changeover contact
- TU Reset push button
- S51 250V trip indicator



General Information

Brand	ABB
Product Type	Automatic ACB
Version	Fixed

Technical Attributes

Design of Control Element	Push Button
Breaking Capacity 400V AC - Icu (kA)	66
Current Type	AC
Earth Fault Protection	Yes
Indication	Switched-off Indicator
Main Circuit Electrical Connection	Bolt Connection
Main Current Circuit Connection Position	Back Side
No. of Auxiliary Change-over Contacts	4
No. of Poles	3
Overload Release Current Setting (A)	800
Power Loss (W)	212
Rated Current (A)	2000
Rated Impulse Withstand Voltage (kV)	12
Rated Instantaneous Short-Circuit Current - Ii (A)	3000
Rated Insulation Voltage AC (V)	1000
Rated Short-time Withstand Current - Icw (kA/1s)	66
Rated Short-time Withstand Current - Icw (kA/3s)	50

Technical Attributes

Rated Uninterrupted Current - I _u (A)	2000
Rated Voltage (V)	690
Terminal Type	Rear Flat Horizontal

Dimensions

Dimensions (mm)	276W x 371H x 270D
Size of Frame	E2.2

Protection & Standards

Degree of Protection	IP30
----------------------	------