

Product No: CSXi045V4C2

AuCom CSXi045V4C2 SOFT STARTER 45KW 85A 200-440VAC, CONTROL 24VAC/DC

FEATURES

- - 18A ~ 200A Complete with Internal Bypass.
- - Mains voltage: 200~440VAC (V4).
- - Protection: IP20/IP00, 3 frames sizes.
- - Soft Start and Soft Stop Motor overload, Phase sequence. protection and Excess start time.
- - 7 Adjustments: Current ramp, Current limit, Motor trip class, Soft stop time, Excess start time, Auxiliary relay function, Phase sequence protection.
- - Compact and light weight.
- - Integrated bypass contactors.
- - Motor protection against operational overload, current spikes & fluctuations.
- - Plug-in communication interfaces.
- - Insulating finger guards.



General Information

Brand	AuCom
Product Type	Compact & Simple - CSXi

Technical Attributes

Current Consumption (A)	2 (At power-up)
EMC Emission	Equipment Class - A
Heat Dissipation During Run (W)	10 (Typical)
Heat Dissipation During Start (W/A)	3
Input Voltage AC (V)	Start: NO 300 (Max.)/ Stop: NC 300 (Max.)
Motor Power - Medium Duty 400-415V (kW)	45
Rated Control Supply Voltage AC/DC (V)	24
Rated Current - Heavy Duty (A)	73
Rated Current - Medium Duty (A)	85
Rated Supply Voltage AC (V)	200 - 440

Physical Attributes

Operational Temperature Range (°C)	-10 to +60
------------------------------------	------------

Dimensions

Dimensions (mm)	145W x 215H x 193D
-----------------	--------------------

Protection & Standards

Degree of Protection	IP20
----------------------	------


Pollution Degree	3
------------------	---

Standards and Approvals	C-tick, UL / C-UL, CE, CCC, Lloyds
-------------------------	------------------------------------

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------

DIMENSIONS



W (mm)	145
H (mm)	215
D (mm)	193
A (mm)	124
B (mm)	196
C (mm)	-
D (mm)	110.5
E (mm)	37