

Product No: 274032

STAHL 6149/2-5611-5010 LED INSPECTION LIGHT 274032

FEATURES

- LED inspection light suitable for hazardous areas
- Operational voltage range of 110 to 240 VAC or DC
- Nominal current of 0.130 A with a power consumption of 13 W
- Equipped with a single-row LED in neutral white color temperature
- Features a diffuser for even light distribution
- Operating temperature range from -30 °C to +60 °C
- High ingress protection rated at IP66/IP67 for dust and water resistance
- Designed for surface mounting applications
- Certified for use in explosive atmospheres (ATEX/IECEx)

General Information

Brand	STAHL
Series	6149

Technical Attributes

Nominal Output Current (A)	0.13
Nominal Power (W)	13
Rated Maximum Operational Voltage AC (V)	240
Rated Maximum Operational Voltage DC (V)	240
Rated Minimum Operational Voltage AC (V)	110
Rated Minimum Operational Voltage DC (V)	110
Rated Operational Current (A)	0.13

Physical Attributes

Maximum Temperature (°C)	40
Minimum Temperature (°C)	-30
Mounting Type	Surface



Protection & Standards

Degree of Protection	IP66/67
Standards and Approvals	ATEX/IECEx

Resources

Product catalogue (Flipbook)	Download from here
------------------------------	------------------------------------