

CA781/2



**connectwell**  
THE RIGHT CONNECTION

ca781, pre assembled shorting link, jumper, cross connection, cross connection bridge

Internal Shorting Link Assemblies consist of a Current Bar shorting Sleeves and Screws. They install easily into the centre of the Terminal Block and connect to the current bar. They are available as standard 2, 3, 4, 10 or 100 pole assemblies and are ready for immediate installation. Insulated pre assembled shorting link assemblies provide shock protection when installed on Terminal Blocks.

**PRODUCT SPECIFICATION**

Rated Current	125 A
Torque	0.8 Nm

**ORDERING INFORMATION**

CAT. NO.	DESCRIPTION	STD. PACK
CA781/2	Insulated Pre assembled Shorting Link for 2 way shorting	50
CA781/3	Insulated Pre assembled Shorting Link for 3 way shorting	20
CA781/4	Insulated Pre assembled Shorting Link for 4 way shorting	20
CA781/10	Insulated Pre assembled Shorting Link for 10 way shorting	10

**SUITABLE FOR**

CTS35UNCRV0	35 sq.mm Feed Through Corrosion Resistant Terminal Blocks
CTS35UNV0	35 sq.mm Feed Through Terminal Blocks with Slotted Screws
CTS35UNA	35 sq.mm Feed Through Terminal Blocks with Allen Screws
CTS35UN	35 sq.mm Feed Through Terminal Blocks with Slotted Screws